PowerScale F200 All-Flash Specifications

F200 ATTRIBUTES & OPTIONS	960 GB SSD	1.92 TB SSD	3.84 TB SSD
Raw node capacity	3.84 TB	7.68 TB	15.36 TB
SSD drives (2.5") per node	4		
Self-encrypting drive (SED SSD) option	No		
Operating system	PowerScale OneFS 9.0		
CPU type (per node)	Single socket Intel® Processor		
ECC memory (per node)	48 GB or 96 GB		
Front-end networking (per node)	2 x 10 GbE (SFP+) or 2 x 25 GbE (SFP28)		
Infrastructure networking (per node)	2 x 10 GbE or 2 x 25 GbE (SFP28)		
Typical power consumption @ 240v (per node)	239 Watts (@25°C)		
Max power consumption @ 240v (per node)	394.6 Watts		
Typical thermal rating	815.5 BTU/hr		

PowerScale F600 All-Flash Specifications

F600 ATTRIBUTES & OPTIONS	1.92 TB SSD	3.84 TB SSD	7.68 TB SSD
Raw node capacity	15.36 TB	30.72 TB	61.44 TB
NVMe SSD drives (2.5") per node	8		
Self-encrypting drive (SSD SED) option	No		
Operating system	PowerScale OneFS 9.0		
CPU type (per node)	Dual Socket Intel® Processor		
ECC memory (per node)	128, 192 or 384 GB		
Front-end networking (per node)	2 x 10GbE (SFP+) or 2 x 25 GbE (SFP28) or 2 x 100 GbE (QSFP28+)		
Infrastructure networking (per node)	2 x 100 GbE (QSFP28+)		

Finite IT.

0844 225 0482 I sales@finite-it.com I www.finite-it.com